

## MATERIAL SAFETY DATA SHEET

#### SECTION 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: PM101 DIFF/GEARLIFE 85W140 GL-5

Product Code: 101

Product Use: Lubricating Oil, Gears

**Supplier: PM Lubrication (ABN 95 880 856 055)** 

4/105 Archibald Street, Mackay Queensland, 4740 Australia

Phone: +61 (07) 4998 5851

EMERGENCYNUMBER: 1800 033 111 (Australia)

Chemical Nature: Petroleum derived Lubricating Oil

Creation Date: Feb 2021

This version issued: Jan 2023 and is valid for 5 years from this date

SECTION 2 - HAZARDS IDENTIFICATION

Classification of the substance or mixture
GHS Classification:

Mixture

Classified as Hazardous Substance, Non-Dangerous Goods, according to Australian WHS

Regulations and ADG Code: Chronic Toxicity Category 4; Acute Toxicity Category 3

Eye Irritant Category 2B

Other Hazards which do not result

Defatting to the skin.

in classification:

Used oil may contain hazardous components which have the

potential to cause skin cancer.

See Toxicological Information (Section 11 of this Safety Data

Sheet)

**Label Elements** 

Hazard pictograms: No pictogram required

Signal Word: Warning

Hazard Statements: H413: May cause long lasting effects to aquatic life

H402: Harmful to aquatic life H320: Causes eye irritation

Precautionary statements

P273: Avoid release to the environment

**Response:** P264: Wash off with soap and plenty water or use recognised skin cleanser.

P305+351+338: IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses if present

and easy to do – continue rinsing. P337+313: If eye irritation persists - **Get Medical Advice/Attention** 

Storage: Not applicable

**Disposal:** P501: Dispose of contents and container in accordance

with all local, regional, national and international

regulations

**Supplemental label elements:** Safety Data Sheet available on request

Special packaging requirements

Containers to be fitted with child

resistant fastenings: Not applicable
Tactile warning of danger: Not applicable

PAGE 2 OF 15 THIS VERSION ISSUED JAN. 2023

## SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture Chemically modified base oil. Proprietary performance additives

Mixture

Product/Ingredient	%	CAS	Hazard	Risk Phrase/Hazard
Name		Number	Classification	Statements
Distillates (petroleum,	60 -	64742-54-7	Not classified	Not applicable
hydrotreated light	100			
paraffinic				
Mineral oil	60 –	Mixture*	Not classified	Not applicable
	100			
Long chain alkaryl amine	0.1 -	Trade	Aquatic chronic	P501/H413
	0.5	Secret	Cat 4	
Zinc	0.5-1.0	84605-29-8	Eye damage Cat. 1	P273, P280, P310
Dialkydithiophosphate			Chronic Toxicity	P305+P351+P338+p501/H303
			Cat. 2	H315, H318, H411, H401

<sup>\*</sup>The mineral oil contained in this material may be described by one or more of the following: CAS Nos: 64742-65-0, 64742-55-8 and 64742-56-9

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8

## SECTION 4 - FIRST AID MEASURES

Description of first aid measures

Eye Contact In case of contact with eyes, immediately flush eyes with plenty of

water for at least 15 minutes. Keep eye wide open while rinsing.

Remove any contact lenses. Seek medical advice

Skin Contact Wash off with soap and plenty of water or use recognized skin

cleanser. Take off contaminated clothing and shoes immediately.

Get medical attention if irritation develops.

**Inhalation** If inhaled, remove to fresh air. Get medical attention if symptoms

appear.

**Ingestion** Do not induce vomiting unless directed to do so by medical personnel.

Get medical attention if symptoms occur or contact a Poisons

Information Centre on 13 11 26 (Australia)

Protection of First Aiders No action shall be taken involving any personal risk or without

suitable training.

Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on

health effects and symptoms.

Indication of any immediate medical attention and special

Treatment should in general be symptomatic and directed

to relieving any effects.

treatment needed notes to physician -.

PAGE 3 OF 15 THIS VERSION ISSUED JAN 2023

## **SECTION 5 - FIRE FIGHTING MEASURES**

## **Extinguishing Media:**

Suitable Extinguishing Media In case of fire, use foam, dry chemical or carbon dioxide

extinguisher or spray.

Unsuitable Extinguishing Media Do not use water jet.

## Special Hazards arising from the substance or mixture

Hazards from the substance In a fire or if heated, a pressure increase will occur and the

of mixture container may burst.

Hazardous combustion products Combustion products may include the following:

Carbon oxides (CO, CO2) (carbon monoxide, carbon

dioxide).

**Advice for Fire Fighters** 

Special Precautions for Fire Fighters Promptly isolate the scene by removing all persons from

the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

Special Protective Equipment

For Fire Fighters

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire fighters (including helmets, protective boots and gloves) conforming to European Standard EN469 or the relevant standards will provide a basic level of protection for chemical

incidents.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

## Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personal No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective

equipment.

For Emergency Responders If specialised clothing is required to deal with the spillage, take

note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency

personnel."

Environmental Precautions Avoid dispersal of spilt material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers,

waterways, soil or air).

Issued by: PM Lubrication Phone: (07) 4998 5851 Mob: 0419 771 825

www.pmlubrication.com.au

hello@pmlubrication.com.au

Poisons Information Centre: 13 11 26 from anywhere in Australia

PAGE 4 OF 15 THIS VERSION ISSUED JAN 2023

## SECTION 6 - ACCIDENTAL RELEASE MEASURES (CONT.)

## Methods and Material for containment and cleaning up

Small Spill Stop leak if without risk. Move containers from spill area. Absorb

with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large Spill Stop leak if without risk. Move containers from spill area. Prevent

entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and shovel/place in container for disposal according to local regulations. Dispose of

via a licensed contractor

**Reference to other Sections** See Section 1 for Emergency Contact information.

See Section 5 for firefighting measures.

See Section 8 for information on appropriate personal protective

equipment.

See Section 12 for environmental precautions.

See Section 13 for additional waste treatment information

#### SECTION 7 - HANDLING AND STORAGE

## Precautions for safe handling

Protective measures Put on appropriate personal protective equipment.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas. where this material is handled, stored, and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled

containers.

Not suitable Prolonged exposure to elevated temperature.

Specific end use(s)

Recommendations See Section 1.2 and Exposure scenarios in annex, if applicable

Issued by: PM Lubrication Phone: (07) 4998 5851 Mob: 0419 771 825

www.pmlubrication.com.au hello@pmlubrication.com.au

Poisons Information Centre: 13 11 26 from anywhere in Australia

PAGE 5 OF 15 THIS VERSION ISSUED JAN 2023

## **SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION**

#### **Control Parameters**

## Occupational exposure limits

## Product/Ingredient name

Ingredient Name	Exposure Limits		
Distillates (petroleum), hydrotreated	ACGIH TLV (United States)		
heavy paraffinic	TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised:		
	11/2009 Form: Inhalable fraction		
Base oil - unspecified	ACGIH TLV (United States)		
	TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised:		
	11/2009 Form: Inhalable fraction -		
Distillates (petroleum), solvent-	ACGIH TLV (United States)		
dewaxed heavy paraffinic	TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised:		
	11/2009 Form: Inhalable fraction		

Recommended Monitoring Procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation, or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace Atmospheres - guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy); European Standard EN 14042 (Workplace Atmospheres - guide for the application and use of procedures for the assessment of exposure to chemical and biological agents); European Standard EN 482 (Workplace Atmospheres - general requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level
Predicted No Effect
Concentration
Exposure Controls

No DNELs/DMELs available No PNECs available

# Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organization for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Issued by: PM Lubrication Phone: (07) 4998 5851 Mob: 0419 771 825

www.pmlubrication.com.au

Poisons Information Centre: 13 11 26 from anywhere in Australia

PAGE 6 OF 15 THIS VERSION ISSUED JAN 2023

## SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION (CONT>)

## **Environmental exposure controls**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory Protection

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable The correct choice of respiratory respiratory equipment. protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore chosen be in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection

Safety glasses with side shields

## **Skin Protection**

Skin and body

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required

PAGE 7 OF 15 THIS VERSION ISSUED JAN 2023

## SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION (CONT.)

Hand Protection

General information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposure).

Gloves should be chosen in consultation with the supplier/manufacturer and taking account of a full assessment of the working conditions.

**Recommended: Nitrile Gloves** 

Breakthrough time

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type.

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes or >480 minutes if suitable gloves can be obtained. If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term/Splash protection:

Recommended breakthrough times as above. It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times my commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

**Glove Thickness** 

For general applications, we recommend gloves with a thickness typically greater than 0.35mm. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Issued by: PM Lubrication Phone: (07) 4998 5851 Mob: 0419 771 825

www.pmlubrication.com.au

hello@pmlubrication.com.au

Poisons Information Centre: 13 11 26 from anywhere in Australia

PAGE 8 OF 15 THIS VERSION ISSUED JAN 2023

## SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION (CONT.)

Note: Depending on the activity being conduction, gloves of Glove Thickness (Cont.)

varying thickness may be required for specific tasks. For

example:

Thinner gloves (down to 0.1mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

Thicker gloves (up to 3mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e.

where there is abrasion or puncture potential

**Environmental Exposure Controls** Emissions from ventilation or work process equipment should

be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable

levels.

#### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

#### Appearance:

Physical State Liquid Colour (ASTM D1500) DYED RED Odour Not available Odour threshold Not available Not available Hq

Melting point/freezing point Not available Initial boiling point and boiling range Not available

Pour point (ASTM D97, (°C) -27 Flash point (ASTM D92), (°C) 216

Not available Evaporation rate Flammability (solid, gas) Not available Upper/lower flammability of explosive limits Not available Vapour pressure Not available

Vapour density Not available Relative density Not available

Density (ASTM D4052) @15 °C, (g/cm3) 0.877

Not soluble in water Solubility(ies)

Partition coefficient: n-octanol/water >3 Auto-ignition temperature 336

Issued by: PM Lubrication Phone: (07) 4998 5851 Mob: 0419 771 825 www.pmlubrication.com.au hello@pmlubrication.com.au Poisons Information Centre: 13 11 26 from anywhere in Australia

PAGE 9 OF 15 THIS VERSION ISSUED JAN 2023

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES (CONT.)

Information on basic physical and chemical properties Appearance (Cont.)

Decomposition temperature Not available

Kinematic Viscosity (ASTM D445) @40 °C, (cSt) 193 Kinematic Viscosity (ASTM D445) @100 °C,(cSt 18

Explosive properties Not available Oxidising properties Not available

#### SECTION 10 - STABILITY AND REACTIVITY

Reactivity No specific test data available for this product.

Refer to Conditions to Avoid and Incompatible Materials for

additional information.

Chemical stability The product is stable

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous

reactions will not occur.

Under normal conditions of storage and use, hazardous

polymerisation will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame)

Incompatible materials Reactive or incompatible with the following materials:

Oxidising materials

decomposition products should not be produced.

## **SECTION 11 – TOXICOLOGICAL INFORMATION**

## **Information on Toxicological Effects**

#### **Acute Toxicity Estimates**

Route	ATE Value
Not available	200,000

# Information on the likely routes of exposure: Routes of entry anticipated: Dermal, Inhalation Potential acute health effects

Inhalation Vapour inhalation under ambient conditions is not normally a

problem due to a low vapour pressure

Ingestion No known significant effects or critical hazards

PAGE 10 OF 15 THIS VERSION ISSUED JAN 2023

## SECTION 11 - TOXICOLOGICAL INFORMATION (CONT.)

## Potential acute health effects (Cont.)

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Eye contact No known significant effects or critical hazards

## Symptoms related to the physical, chemical and toxicological characteristics

Inhalation No specific data Ingestion No specific data

Skin contact Adverse symptoms may include the following:

Irritation Dryness Cracking

Eye contact No specific data

## Delayed and immediate effects and also chronic effects from short and long term exposure

Inhalation Over exposure to the inhalation of airborne droplets or aerosols may

cause irritation of the respiratory tract.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation

and/or dermatitis.

Eye contact Potential risk of transient stinging or redness if accidental eye contact

occurs.

## Potential chronic health effects

General USED LUBRICANT OILS

Used oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used oil must therefore be avoided and a high standard of

personal hygiene maintained.

Carcinogenicity

No known significant effects or critical hazards

PAGE 11 OF 15 THIS VERSION ISSUED JAN 2023

#### **SECTION 12 - ECOLOGICAL INFORMATION**

**Toxicity** 

Environmental hazards Not classified as dangerous.

Based on data available for this or related materials No known significant effects or critical hazards.

Persistence and degradability Expected to be biodegradable

Bio-accumulative potential

This product is not expected to bioaccumulate through

food chains in the environment.

96hr LC50 (for fish), mg/l >1000 48hr EC50 (for crustacean), mg/l >1000 72 or 96 hr ErC50 (for algae or other aquatic >1000

Mobility in soil

Soil/water partition coefficient (KOC)

Not available

Mobility Spillages may penetrate the soil causing ground

water contamination.

Results of PBT and vPvB assessment

PBT Not applicable vPvB Not applicable

Other adverse effects

Other ecological information Spills may form a film on water surfaces causing

physical damage to organisms. Oxygen transfer could

also be impaired.

#### SECTION 13 - DISPOSAL CONSIDERATIONS

## **Disposal Methods**

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should, at all times, comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and run off and contact with soil, waterways, drains and sewers

#### **Waste Treatment Methods Product**

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an

authorized person/licensed waste disposal contractor in accordance with

local regulations.

Hazardous waste Yes

## **SECTION 13 - DISPOSAL CONSIDERATIONS (CONT.)**

PAGE 12 OF 15 THIS VERSION ISSUED JAN 2023

## .European waste catalogue (EWC)

Waste Code	Waste Designation	
13 02 05*	Mineral-based non-chlorinated engine, gear and lubricating oils	

<sup>\*</sup>However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

**Packaging** 

Methods of Disposal Where possible, arrange for product to be recycled.

Dispose of via an authorized person/licensed waste disposal contractor in accordance with local regulations.

Special precautions

This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal o split material and runoff and contact with soil, waterways, drains and sewers.

#### **SECTION 14 - TRANSPORT INFORMATION**

Land (as per ADG classification)

Not regulated. This material is not classified as

dangerous under ADG Code

IMDG This material is not classified as dangerous under IMDG

regulations.

IATA (Country variations may apply)

This material is either not classified as dangerous under

IATA regulations or needs to follow country specific

requirements.

	Land Transport (ADG)	Sea Transport (IMDG/IMO	Air Transport (IATA/ICAO)
UN number	Not regulated	Not regulated	Not regulated
UN property shipping name	Not regulated	Not regulated	Not regulated
Transport hazard (class(es)	Not regulated	Not regulated	Not regulated
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	No	No	No
Special precautions for user	-	-	-

Special precautions for user - Not available

PAGE 13 OF 15 THIS VERSION ISSUED JAN 2023

#### SECTION 15 - REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Substances of very high concern None of the components are listed

Safety, health and environmental regulations specific for the product

No known specific national and/or regional regulations applicable to this product (including its ingredients).

Poison schedule A poison schedule number has not been allocated

> to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons

(SUSMP)4

Classifications Safework Australia criteria is based on the Globally

Harmonised System (GHS) of Classification and

Labelling Chemicals

The classifications and phrases listed below are based

on the Approved Criteria for Classifying Hazardous

Substances None allocated

Risk phrases None allocated Safety phrases None allocated Inventory listing(s) All components are listed on ACIS or are exempt

Regulation according to other foreign laws

**REACH Status** For the REACH status of this product please consult your

company contact, as identified in Section 1

United States Inventory (TSCA 8b)

Australia Inventory (AICS) Canada Inventory

Hazard codes

China Inventory (IECSC) Japan Inventory (ENCS) Korea Inventory (KECI) Philippines Inventory (PICCS)

Chemical Safety Assessment

All components are listed and exempted All components are listed and exempted At least one component is not listed

All components are listed and exempted

All components are listed and exempted All components are listed and exempted All components are listed and exempted

This product contains substances for which Chemical

Safety Assessments are still required

Issued by: PM Lubrication Phone: (07) 4998 5851 Mob: 0419 771 825 www.pmlubrication.com.au hello@pmlubrication.com.au Poisons Information Centre: 13 11 26 from anywhere in Australia

PAGE 14 OF 15 THIS VERSION ISSUED JAN 2023

#### SECTION 16 - OTHER INFORMATION

Abbreviations and acronyms: ACGIH = American Conference of Government Industrial

**Hygienists** 

ADG = Australian Dangerous Goods

Code

ADN = European Provisions concerning the International Carriage of

Dangerous Goods by Inland Waterway

ADR =The European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstract Service

CLP = Classification, Labelling and Packaging Regulation

[Regulation (EC) No. 1272/2008] CSA = Chemical Safety Assessment CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

DPD = Dangerous Preparations Directive (1999/45EC)
DSD = Dangerous Substances Directive (67/548/EEC)
EINECS = European Inventory of Existing Commercial

Chemical Substances ES = Exposure Scenario

EMS = Emergency Schedules (Emergency Procedure for

Ships Carrying Dangerous Goods)

ENCS = Existing and New Chemical

Substances

EUH statement = CLP - specific Hazard

statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals IARC = International Agency for Research on

Cancer

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LC50 = Lethal Concentration, 50% / Medium Lethal Concentration

LD50 = Lethal Dose, 50%/Medium Lethal Dose

Log Pow = logarithm of the octano/water partition co-efficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978 (Marpol = marine pollution)

NOHSC = National Occupational Health & Safety Commission

OECD = Organization for Economic Co-operation and Development

OEL = Occupational Exposure Limit

PBT = Persistent, Bio-accumulative and Toxic PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of

Dangerous Goods by Rain

P 15 OF 15 THIS VERSION ISSUED JAN 2023

## **SECTION 16 – OTHER INFORMATION (CONT.)**

RRN = REACH Registration Number

SAA/SNZ HB76 = Dangerous Goods Initial Emergency Response Guide

SADT = Self-Accelerating Decomposition Temperature

STEL - Short Term Exposure Limit

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure

SUSMP = Standard for the Uniform Scheduling of Medicines and Poisons

SVHC = Substances of Very High Concern

SWA = Safe Work Australia TLV = Threshold Limit Value

TSCA = Toxic Substance Control Act

TWA = Time weighted average

UN = United Nations

UVCB = Complex hydrocarbon substance

VOC - Volatile Organic Compound

vPvB = Very Persistent and Very Bio-accumulative

WHS = Work Health and Safety Regulations

History

This version Date of Issue Prepared by 24 January 2023

Bernadini Pty Ltd T/as Lubricant Specialists Australia (LSA)

Indicates information that has changed from previously issued version.

#### Notice to reader:

All reasonable, practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified above. No warranty or representation, express or implied, is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from PM Lubrication.

It is the User's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. PM Lubrication shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material; from any failure to adhere to recommendations; or from any hazards inherent in the nature of the material.

Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any personal handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact PM Lubrication to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Issued by: PM Lubrication Phone: (07) 4998 5851 Mob: 0419 771 825

www.pmlubrication.com.au

hello@pmlubrication.com.au

Poisons Information Centre: 13 11 26 from anywhere in Australia