



MATERIAL SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: PM208 POWER ON TRAX 4T
Product Code: 208
Product Use: Engine Lubrication Oil
Supplier: PM Lubrication (ABN 95 880 856 055)
4/105 Archibald Street, Mackay
Queensland, 4740 Australia
Phone: +61 (07) 4998 5851

EMERGENCY

TELEPHONE NUMBER: 1800 033 111 (Australia)

Chemical Nature: Petroleum derived Lubricating Oil

Creation Date: Feb. 2021

This version issued: Feb. 2021

INGREDIENTS:

Refined mineral and chemical additives – not hazardous according to SWA

PHYSICAL DATA:

Flash Point C Typical > 200°C
Boiling Point > 250°C
Solubility in Water Negligible

FIRE AND EXPLOSION HAZARD DATA:

Flash Point over 170°C. Will not burn unless heated to high temperatures
Extinguish fires with CO₂, Dry Chemical, Foam or BCF
Fire fighters should wear self-contained breathing apparatus if fire is in poorly ventilated area and is too large for hand-held extinguisher.

HEALTH HAZARD DATA:

EYE CONTACT: May cause mild irritation
SKIN CONTACT: May cause mild irritation
INHALATION: May cause mild throat or nose irritation if inhaled at elevated temperatures
SWALLOWED: May cause mild gastric irritation

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: Flush with water for 15 – 20 minutes
SKIN CONTACT: Wash with soap and water
INHALATION: Remove to fresh air
SWALLOWED: Do **NOT** induce vomiting

In all cases seek medical attention if discomfort persists

REACTIVITY DATA:

INCOMPATIBILITIES: Strong Oxidisers
 Hazardous decomposition product
 Product is considered unstable

SPILL OR LEAK PROCEDURE:

Contain spill and shut off all sources of possible ignition
Absorb on fire retardant material, sand or earth
Follow State or Local Authority regulations for disposal

STORAGE AND HANDLING PROCEDURE:

Not defined as Dangerous Goods for transport by road or rail
Store away from heat, oxidizing agents, foodstuffs and clothing. No health risks are expected as a result of normal handling.

WHERE THE INFORMATION PROVIDED IN THIS BULLETIN INDICATES A POTENTIAL HAZARD, ADEQUATE WARNING SHOULD BE GIVEN TO ALL

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified above. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet. The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from PM Lubrication. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. PM Lubrication shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected, of any hazards described in this sheet and of any precautions that should be taken. You can contact PM Lubrication to ensure that this document is the most current available. Alteration of this document is strictly prohibited.