

MATERIAL SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	PM400 NEWLIFE ENGINE FLUSH 10W	
Product Code:	400	
Product Use: Supplier:	Petroleum Degreaser PM Lubrication (ABN 95 880 856 055) 4/105 Archibald Street, Mackay Queensland, 4740 Australia	
	Phone: +61 (07) 4998 5851	
EMERGENCY TELEPHONE NUMBER: <	1800 033 111 (Australia)	
Chemical Nature:	Petroleum Hydrocarbon	
Creation Date:	25 Sept 2005	
This version issued:	8 July 2024	

SECTION 2 – HAZARDS IDENTIFICATION

Statement of Hazardous Nature

This product is CLASSIFIED according to Safe Work Australia CriteriaThis product is NOT CLASSIFIED as a Dangerous Good by the Criteria of the ADG CodeUN No:None allocatedDG Class:None AllocatedSubsidiary Risk(s):None AllocatedPacking Group:None allocatedHazchem Code:None allocated

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
Butyldiglycol	Not available	112.34.5	>4
All other ingredients considered Non- Hazardous	Not available		

Page 2 of 7. This version issued 8 July 2024

SECTION 4 – FIRST AID MEASURES

- **Eye:** If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
- **Inhalation:** If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
- **Skin:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons I nformation Centre or a doctor.
- **Ingestion**: For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
- Advice to Doctor: Treat symptomatically

SECTION 5 – FIRE FIGHTING MEASURES

- Flammability: Combustible. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.
- **Fire & Explosion:** Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use water-fog to cool intact containers and nearby storage area.
- **Extinguishing:** Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.
- HazChem Code: None allocated

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Spillage: Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover/absorb spill with non-combustible absorbent material (vermiculite, sand or similar), collect and place in suitable containers for disposal.

Page 3 of 7. This version issued 8 July 2024

SECTION 7 – STORAGE AND HANDLING

- Storage: Store in a cool, dry, well-ventilated area, removed from oxidising agents, acids, alkalis, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire protection systems. Store as a Class C2 Combustible Liquid (AS1940).
- **Handling**: Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

SECTION 6 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Stds

Ingredient	Reference	Т٧	VA	ST	EL
Mineral oil mist	SWA (Aus)	-	5mg/m3	-	-

Biological Limits: No biological limit allocated.

EngineeringAvoid inhalation. Use in well-ventilated areas. Where an inhalationControls:risk exists, mechanical extraction ventilation is recommended. Maintain
vapour levels below the recommended exposure standard.

PPE: Wear splash-proof goggles and rubber or PVC gloves. When using large quantities or where heavy contamination is likely, wear: coveralls. Where an inhalation risk exists, wear: a Type A (Organic vapour) respirator. With prolonged use, wear: viton (R) or nitrile gloves and coveralls.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear Bright Liquid	Solubility (Water)	Insoluble
Odour	Characteristic Odour	Specific Gravity	0.860 to 0.870
0 to pH	Not Relevant	% Volatiles	Not Available
Vapour Pressure	Not Available	Flammability	Class C2
			Combustible
Vapour Density	Not Available	Flash Point	>196°C
Boiling Point	Not Available	Upper Explosion Limit	Not Available
Melting Point	Not Available	Lower Explosion Limit	Not Available
Evaporation Rate	Not Available		
Pour Point	-16°C	Viscosity	20 cSt-22 cSt @
			40°C

SECTION 10 STABILITY AND REACTIVITY

Chemical Stability:	Stable under recommended conditions of storage				
Conditions to Avoid:	Avoid heat, sparks, open flames and other ignition sources				
Material to Avoid:	Incompatible with oxidising agents (eg. Hypochlorites), acids (eg. Nitric Acid), alkalis (eg. Hydroxides), heat and ignition sources				
Hazardous Decomposition Prod	May evolve toxic gases (carbon oxides, hydrocarbons) when heated ucts: to decomposition				
Hazardous Reactions	s: Polymerization is not expected to occur				
	SECTION 11 TOXICOLOGICAL INFORMATION				
Health Hazard Summary:	Low toxicity. Use safe work practices to avoid eye or skin contact and inhalation. The mineral oil contained within this product is highly refined and therefore is not classifiable as to its carcinogenicity in humans (IARC Group 3)				
Eye:	Low to moderate irritant. Contact may result in irritation, lacrimation, pain and redness				
Inhalation:	Low irritant. Over exposure may result in irritation of the nose and throat, with coughing				
Skin:	Low irritant. Prolonged or repeated contact may result in mild irritation, rash and dermatitis				
Ingestion:	Low toxicity. Ingestion of large quantities may result in nausea, vomiting, abdominal pain, diarrhoea, and drowsiness. Aspiration may result in chemical pneumonitis and pulmonary oedema				
Toxicity Data:	No LD50 data available for this product				
SECTION 12 ECOLOGICAL INFORMATION					
	Mineral oils biodegrade slowly and should not be released to waterways or soil. They can float on water, restricting oxygen exchange with possible asphyxiation of aquatic life.				
Ecotoxicity:	Not classified as dangerous to the aquatic environment.				
Persistence/ Degradability:	Expected to be inherently biodegradable				
Mobility:	Low solubility and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.				

Issued by: PM Lubrication Phone: (07) 4998 5851 Mob: 0419 771 825 <u>www.pmlubrication.com.au</u> hello@pmlubrication.com.au Poisons Information Centre: 13 11 26 from anywhere in Australia

Page 5 of 7. This version issued 8 July 2024

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Disposal:	Reuse where possible or return to manufacturer/supplier. May be recycled. Do not release to drains or waterways			
	Contact the manufacturer for additional information			
Legislation:	Dispose of in accordance with relevant local legislation			

SECTION 14 TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name:	None Allocated	DG Class:	None Allocated
UN No:	None Allocated	HazChem Code:	None Allocated
Packing Group:	None Allocated	Subsidiary Risk(s):	None Allocated

SECTION 15 REGULATORY INFORMATION

Poison Schedule: A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP)

AICS: All chemicals listed on the Australian Inventory of Chemical Substances (AICS)

SECTION 16 OTHER INFORMATION

MINERAL OILS - SOLVENT REFINED: Animal experiments and human experience have not shown cancer risks when handling solvent refined mineral oils, unlike non refined mineral oils. CLEANING MINERAL OIL

CONTAMINATED CLOTHING: Cleaners are advised that when cleaning oil contaminated clothing it is essential that freshly distilled solvent is used for each batch, including final rinse, as even filtered solvent will leave oil residues.

SECTION 16 OTHER INFORMATION (CONT.)

MINERAL OILS – USED: Used mineral oils in engine crankcases and other high temperature/high stress environments may contain potentially harmful residues, some of which have been shown to cause irreversible skin effects, including cancer. Prolonged and repeated inhalation of mists associated with used mineral oils may result in pulmonary fibrosis.

MINERAL OILS: - INJECTION; Where high pressure applications are used the risk of accidental injection under the skin exists and may result in an extremely painful and serious injury requiring immediate medical attention. Depending on the pressure used, mineral oils may be injected a considerable distance below the skin and may cause permanent tissue damage.

SEEK IMMEDIATE MEDICAL ATTENTION. EXERCISE EXTREME CARE WHEN USING HIGH PRESSURE EQUIPMENT.

ABBREVIATIONS:

ACGIH - American Conference of Industrial Hygienists. ADG - Australian Dangerous Goods. **BEI** - Biological Exposure Indice(s).

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds. **CNS** - Central Nervous System.

EC No - European Community Number.

HSNO - Hazardous Substances and New Organisms.

IARC - International Agency for Research on Cancer. mg/m3 - Milligrams per Cubic Metre. **NOS** - Not Otherwise Specified.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). **ppm** - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances

STEL - Short Term Exposure Limit.

SWA - Safe Work Australia.

TWA - Time Weighted Average.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

SECTION 16 OTHER INFORMATION (CONT.)

Report Status

This document has been compiled by Tru Blu Oil, the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While Tru Blu Oil has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, Tru Blu Oil accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified above. No warranty or representation, express or implied is made as to the accuracy of completeness of the data and information in this data sheet. The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from **PM Lubrication**. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. **PM Lubrication** shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected, of any hazards described in this sheet and of any precautions that should be taken. You can contact **PM Lubrication** to ensure that this document is the most current available. Alteration of this document is strictly prohibited.