

PM107

Multi-GearLife EP MP
Limited Slip Application
SAE 85W140 GL-5 J2360

XHT Xtra High Temperature

Product Information

PM107 Multi Gearlife 85W140 XHT- Xtra High Temperature, is a superior new generation extreme pressure (EP) gear oil for limited-slip differential performance and tackifiers to enhance such performance. PM 107 will in most instances reduce operating temperatures over conventional EP lubricants. Users will benefit greatly from the exceptional thermal stability of the oil derived from the base oil quality and additive treatment to maintain minimal sludge or gum deposits. Special oxidation-resistant synthetic and other base stock combined with high-performance additives enable uniformly controlled viscosity throughout the operating temperature range to ensure the cooler running of the machinery resulting in extension of the lubricant and component life.

PM107 Multi GearLife satisfies the first choice for initial and service fill or even top-up of manual transmissions, differentials, including limited-slip, final drives, transfer cases, and steering boxes in trucks coaches, industrial, agricultural gear cases, and OEM equipment requiring this specification.

PM107 Multi GearLife XHT adhesive properties effectively quieten drive train GEAR RATTLE in low speed - high torque, high speed - low torque operations. Protection from yellow metal corrosion.

PM Lubrication Friction Reduction Technology is Engineered into this Gear Oil.

Typical Properties:

SAE Viscosity	85W140
Kinematic Viscosity	
Viscosity @ 40°C	402 cSt
Viscosity @ 100°C	26.2 cSt
Pour Point °C	-24
Flash Point, COC °C	251
Colour	Red
V.I.	TBA
Thermal Oxidation Stability (CRC L60)	Pass
Density @ 15°C kg/L	0.911

Exceeds Service Classifications:

- API GL-5, MT-1
- MIL-L-2105D, MIL-PRF-2105E
- SAE J2360
- Clark
- Daimler Benz
- Eaton Fuller
- Ford
- GM
- Mack GO-J, GO-H
- Volvo

PM107 Multi GearLife XHT
Dramatic Improvement in component
Life and Durability.

Benefits:

- Exceptional Wear Minimization
- NO Yellow Metal Corrosion
- Reduces Friction
- Shear Stable
- Reduces Operating Temperature
- Prolonged Service Life
- Extraordinary Film Strength

DO MORE WITH LESS

Why PM Lubrication?

- ★ Premium Quality
- ★ XPR Protection Reserve
- ★ Cost-Effective Lubrication

Available in 205L, 20L, 5L Containers



PM Lubrication
4/105 Archibald St, Paget
Queensland 4740 Australia
Tel: 07 4998 5851 Mob: 0419 771 825
www.pmlubrication.com.au hello@pmlubrication.com.au

