

High Protection for Cars and Trucks

Product Information

PM118 Multi-GearSyn 75W90 is a synthetic gear oil formulated with PAO base stocks and advanced additive technology, suitable for use in transaxles with hypoid gear arrangements and manual transmissions requiring GL-4 or GL-5. PM118 Multi-GearSyn offers advanced protection against low and high operating temperatures and the harsh conditions encountered in competition. PM118 Multi-GearSyn has extended drain intervals, extremely shear-stable viscosity, compatibility with normal EP gear oils and seals, and the potential to produce lower operating temperatures. PM 118 Multi-GearSyn is suitable for limited-slip applications.

PM118 Multi-GearSyn is also suitable for high-performance cars and commercial differentials, with the added benefit that it already contains the additional additive required by various OEMs for their high-performance differentials.

Other makes include Alfa Romeo, Audi, Jaguar XJ1 220, Porsche, VW, and some Mercedes-Benz models. DAF, ZF, MAN, Eaton, Scania, and other European Truck Driveline applications where this specification and product type are called for.

Features: * Extended Drain intervals. * Excellent high temperature-high load performance. * Shear Stable. * Reduced Operating temperatures. * Compatible with mineral-based EP oils.

Benefits: # Improved component life. # Extended lubricant serviceability. # Increased seal life.

PM Lubrication Low Wear and Friction Reduction Technology is Engineered into this Gear Oil

Typical Properties

SAE Viscosity	75W90
Kinematic Viscosity	
Viscosity @ 40°C	104 cSt
Viscosity @ 100°C	15.5 cSt
Pour Point 0C	TBA
Colour	Red
V>I>	156
Density @ 15° C kg/L	0.876

Benefits

- OEM Endorsed Additive Technology
- Long Lubricant Life
- Mixed Fleet Application
- Reduces Operating Temperature
- Proven Performance
- Proven Low and High Temperature Protection

Meets and or Exceeds Service Classifications

- API GL-5, MT-1, LS 90
- MIL-PRF-2105E
- DAF
- Eaton
- Man 3343 Type S Man 341 Type E3
- MB 235.8
- Scania STO:1
- ZF TE-ML 02B, 05B, 12B, 16F, 17B, 19C, 21B

PM118 Multi-GearSyn 75W90

For Limited Slip & Long Life

Why PM Lubrication?

- ❖ Premium Quality
- ❖ XPR Protection Reserve
- ❖ Cost Effective Lubrication
- ❖ On-Site Monitoring will maximise equipment life
- ❖ Knife Edge Filtration
- ❖ Our Predictive & Preventative Maintenance Programme is **GUARANTEED** to save 15% of your total operating costs

Available in 200L, 20L, 5L, 4 x 5L Containers

Issued January 2026



PM Lubrication
4/105 Archibald St, Paget
Queensland 4740 Australia
Tel: 07 4998 5851 Mob: 0419 771 825
www.pmlubrication.com.au hello@pmlubrication.com.au

