

## Limited Slip Performance

### Product Information

PM118 MultiGearLife Synthetic 75W90 is a full synthetic gear oil formulated from PAO base stocks and advanced additive technology and is suitable for use in transaxles with hypoid gear arrangements and manual transmissions where a GL-4 or GL-5 is called for.

PM118 MultiGearLife Synthetic offers advanced protection against low and high operating temperatures and the harsh conditions that competition conditions generate. PM 118 has capabilities that have an extended drain interval, extremely shear-stable viscosity, and compatibility with normal EP gear oils and seals and will produce lower operating temperatures. PM 118 is suitable for limited slip applications.

PM118 is also suitable for use in high-performance car and commercial differentials with the added bonus that it already contains the additional additive that various OEMs require for their high-performance differentials. Other makes include Alfa Romeo, Audi, Jaguar XJ1 220, Porsche, VW, many European Truck Driveline Applications. See below.

### PM Lubrication Low Wear and Friction Reduction Technology is Incorporated into this Product

#### Typical Properties:

<b>SAE Viscosity</b>	75W90
<b>Kinematic Viscosity</b>	
Viscosity @ 40°C	104 cSt
Viscosity @ 100°C	15.5 cSt
Pour Point °C	
Colour	Red
V.I.	156
Density @ 15°C kg/L	0.876

#### Exceeds Service Classifications:

- API GL-5, MT-1, LS 90
- MIL-PRF-2105E
- DAF
- EATON
- MAN 3343 Type S MAN 341 Type E3
- MB 235.8
- SCANIA STO:1
- ZF TE-ML 02B,05B,12B,16F
- ZF TE-ML 17B,19C,21B

**PM 118 MultiGearLife Synthetic GL-5 MT-1**  
**For Limited Slip & Long Life.**

#### Benefits:

- OEM Endorsed Additive Technology
- Long Lubricant Life
- Mixed Fleet Application
- Reduces Operating Temperature
- Proven Performance
- Proven Low and High Temp Protection

#### Why PM Lubrication?

- ★ Premium Quality
- ★ XPR Protection Reserve
- ★ Cost-Effective

Available in 205L, 20L, 5L Containers



AUSTRALIAN OWNED

