

# PM303

## Multifunctional Transmove III Mineral Based Transmission Fluid

A premium quality, mineral-based automatic transmission and power steering fluid for use in a wide range of makes and models where Dexron® or Mercon performance is required

### Product Information

PM303 Transmove III is manufactured to the latest generation Dexron® III automatic transmission fluid performance. It is also formulated for use in trucks, buses, and heavy-duty machinery that calls for a Dexron® III fluid. The fluid is also recommended for many transmissions used in meeting General Motors and Ford specifications. The product supersedes all previous Dexron®IIE, Dexron®IID and Type-A suffix transmission fluids.

PM303 Transmove III is also suitable in many earlier Japanese vehicles where Dexron® type fluids are called for, such as Toyota- most models prior to 2002, Mazda- up to 2002, Nissan- prior to 2004, Holden all models up to 2006.

PM303 Transmove III may also be used in power steering systems for a significant number of cars, light commercials, and tractors. It is also suitable in many hydraulic systems where an ISO 22 or 32 hydraulic fluid is recommended.

PM Lubrication's **XPR** (Xtra Protection Reserve), has resulted in superior performance in old and late-model vehicles. It has exceptional anti-wear performance, high-temperature protection to resist oxidation, maintaining cleanliness, and improved gear durability and shift feel in cold ambient conditions. Other advantages include increased clutch pack performance and longer transmission life even with high load involvement.

### Typical Properties:

Viscosity@40°C	31.2 cSt
Viscosity@100°C	7.2 cSt
Pour Point	-44°C
Flash Point	200°C
Viscosity Index	206
Colour	Red
Density @15°C Kg/L	0.849

### Approved Service Classifications:

Allison C-4  
Ford Mercon IV  
Ford M2C-138CJ  
General Motors Type A Suffix A  
ATF Dexron®III H IID & II  
Caterpillar TO-2  
Dennison  
BTR Engineering 85LE & 95LE  
Sunstrand

### Benefits:

- Reduces Friction
- Improves Power
- Fuel Conservation
- Lower Wear Rates
- Prolonged Service Life
- Exceptional Cleanliness
- Long Drain

Do NOT use PM303 Transmove III where Dexron® VI, Mercon V or Mercon SP or LV are required.

Available in 205L, 20L, 5L Containers

### Why PM Lubrication?

Maximize your machinery life, saving you THOUSANDS of dollars

Our Predictive and Preventative Maintenance Programme is **GUARANTEED** to save 15% of your total operating costs

