

A Synthetic Transmission Fluid Formulated to Conform to the Frictional Requirements of a Wide Range of Transmissions by Major Manufacturers

Product Information

PM308 Auto-TransLife MP, a full synthetic transmission fluid, is formulated with the latest base stock and additive packs to meet and exceed the specifications of modern transmissions, while delivering exceptional performance ratings in older vehicles that require the exact specifications. PM308 Auto-TransLife MP has been engineered to provide superior thermal stability and sustained protection. The multi-purpose transmission fluid specifications make it suitable for a wide range of passenger and commercial vehicles. PM Lubrication's XPR (Xtra Protection Reserve) delivers superior performance in both older and late-model vehicles. It provides exceptional wear protection, oxidation resistance, sludge and varnish control, and high shear resistance, extending fluid and component life. Frictional stability and low-temperature properties produce smoother performance. PM308 Auto-TransLife MP has excellent oxidation resistance and anti-shudder characteristics. Anti-foaming has also been addressed to ensure optimal fluid dynamics across all lubricated surfaces.

Typical Properties

Viscosity	
Viscosity @ 40°C	35 cSt
Viscosity @ 100°C	7.3 cSt
Pour Point °C	-44 °C
Flash Point COC °C	200 °C
Viscosity Index	180
Colour	Red
Density @ 15° C kg/L	0.846

Benefits

- Reduces Friction
- Improves Power
- Fuel Conservation
- Lower Emissions
- Lower Wear Rates
- Prolonged Service Life
- Exceptional Cleanliness
- Extra Long Drain

Approved Service Classifications

Allison C-4 Allison TES-295 Allison TES-389 Audi G 052 025-A Audi G 052 162-A2 BMW LA2634 LT 71141 Chrysler ATF's Dexron®II, IID, IIIG, IIH, VI Esso LT 71141 FordMercon®V, FordMercon®LV Ford Mercon®SP, Ford Mercon® Honda LV ATF-Z1 Hyundai SP-II, SP-III Idemitsu K17 JASO 1A JWS 3309 KIA SP-II, SP-III MAN 339F, 339 V1 MAN 339 V2, Z1 MAN 339 Z2, 339 Z3	MAZDA ATFIII, ATF-MV BTR 85LE, 95LE MB 236.1, 236.2, 236.5, 236.6 MB 236.7, 236.9, 236.10, 236.81 Mitsubishi Diamond SP-II, SP-III Nissan Matic-D, J, K Shell LA2634 Subaru ATF Texaco TL-7045E, ETL-8072B, N402 Toyota T-III, T-IV+, T-IV Voith 55.6335.XX (607) Voith 55.6335.XX (1363) Volvo 97340 ZF TE-ML 03D, TE-ML 04D ZF TE-ML 09, TE-ML 14A ZF TE-ML 14B, TE-ML 16L ZF TE-ML 17C, ZF Lifeguard 3, 4, 5 speed ZF 6, 7, 8 & 9 speed transmissions use ATF 6FE
---	---

PM308 Auto-TransLife MP

Maximize your machinery life, saving you THOUSANDS

Why PM Lubrication?

- ❖ Premium Quality
- ❖ XPR Protection Reserve
- ❖ Cost Effective Lubrication
- ❖ On-Site Monitoring will maximise equipment life
- ❖ Knife Edge Filtration
- ❖ Our Predictive & Preventative Maintenance Programme is GUARANTEED to save 15% of your total operating costs

Available in 200L, 20L, 5L, 4 X 5L Containers

Issued January 2026



PM Lubrication
4/105 Archibald St, Paget
Queensland 4740 Australia
Tel: 07 4998 5851 Mob: 0419 771 825
www.pmlubrication.com.au hello@pmlubrication.com.au

