

PM308

**Multipurpose
Full Synthetic
Transmission Fluid**

A premium quality, full-synthetic transmission fluid formulated to conform to frictional requirements of a wide range of transmissions by the major manufacturers

Product Information

Product Information PM 308 Multi-purpose full synthetic transmission fluid has been formulated with the latest base stock and additive packs to meet and exceed the specifications of modern transmissions, while also delivering exceptional performance ratings in older vehicles that call for the same specifications.

PM308 has been engineered to promote superior thermal stability that will deliver sustained protection. The multi-purpose transmission fluid specifications make it suitable for a wide range of passenger and commercial vehicles.

PM Lubrication's XPR (Xtra Protection Reserve), has resulted in superior performance in old and late-model vehicles. It has exceptional anti-wear performance, oxidation resistance, sludge and varnish control, and high shear resistance to achieve increased fluid and component life. Frictional stability and low-temperature properties produce smoother performance. PM308 has excellent oxidation resistance and anti-shudder characteristics. Anti-foaming has also been addressed enabling optimum fluid dynamics on all lubricated surfaces.

Typical Specifications:

Viscosity@40°C	35 cSt
Viscosity@100°C	7.3
Pour Point	-44°C
Flash Point	200°C
Viscosity Index	180
Colour	Red
Density @15°C Kg/L	0.846

Approved Service Classifications:

Allison C-4 Allison TES-295 Allison TES-389 Audi G 052 025-A Audi G 052 162-A2 BMW LA2634 LT 71141 Chrysler ATF's Dexron®II, IID, IIIG, IIIH, VI Esso LT 71141 FordMercon®, FordMercon®LV Ford Mercon®SP, Ford Mercon® Honda LV ATF-Z1 Hyundai SP-II, SP-III Idemitsu K17 JASO 1A JWS 3309 KIA SP-II, SP-III MAN 339F, 339 V1 MAN 339 V2, Z1 MAN 339 Z2, 339 Z3	MAZDA ATF-II, ATF-MV BTR 85LE, 95LE MB 236.1, 236.2, 236.5, 236.6 MB 236.7, 236.9, 236.10, 236.81 Mitsubishi Diamond SP-II, SP-III Nissan Matic-D, J, K Shell LA2634 Subaru ATF Texaco TL-7045E, ETL-8072B, N402 Toyota T-III, T-IV+, T-IV Voith 55.6335.XX (607) Voith 55.6335.XX (1363) Volvo 97340 ZF TE-ML 03D, TE-ML 04D ZF TE-ML 09, TE-ML 14A ZF TE-ML 14B, TE-ML 16L ZF TE-ML 17C, ZF Lifeguard 3, 4, 5 speed ZF 6, 7, 8 & 9 speed transmissions use ATF 6FE
--	---

Benefits:

- **Reduces Friction**
- **Improves Power**
- **Fuel Conservation**
- **Lower Emissions**
- **Lower Wear Rates**
- **Prolonged Service Life**
- **Exceptional Cleanliness**
- **Extra Long Drain**

Available in 205L, 20L, 5L Containers

Why PM Lubrication?

Maximize your machinery life, saving you THOUSANDS of dollars

Our predictive & preventative maintenance program is GUARANTEED to save 15% of your total operating costs.



AUSTRALIAN OWNED

PM Lubrication
4/105 Archibald St, Paget
Queensland 4740 Australia
Tel: 07 4998 5851 Mob: 0419 771 825
www.pmlubrication.com.au hello@pmlubrication.com.au

