

## Torque Glide Low Viscosity Manual Transmission Fluid

### Product Information

PM313 Torque Glide is a new-generation, high-performance fluid engineered with Group 2 and 3 base stocks and high-performance additives developed for 4WD and other manual transmissions across a wide range of vehicles that require this specification and require increased protection.

This unique formulation uses the most shear-stable viscosity index modifiers, resulting in enhanced oxidation stability and better component protection than conventional transmission fluids.

PM313 Torque Glide is a tough, low-viscosity fluid noted for reducing stiff or notchy gear changes (cold shift baulk) associated with the highly variable hot and cold conditions characteristic of the Australian climate.

### PM Lubrication Friction Reduction Technology is Engineered into this Gear Oil

### Typical Properties

<b>Viscosity</b>	10W30
Viscosity @ 40°C	82 cSt
Viscosity @ 100°C	13.6 cSt
Pour Point °C	-45 °C
Viscosity Index	170
Colour	Red
Density @ 15°C kg/L	0.846

### Meets and or Service Classifications

- API GL-4
- MIL-L-2105B, C
- Manual Transmission

### PM313 Torque Glide Manual For High Performance

### Benefits

- Smooth Gear Changes
- Low Viscosity
- Shear Stable
- Reduces Operating Temperature
- Prolonged Service Life
- High Load/High Temperature

### Why PM Lubrication?

- ❖ Premium Quality
- ❖ XPR Protection Reserve
- ❖ Cost Effective Lubrication
- ❖ On-Site Monitoring will maximise equipment life
- ❖ Knife Edge Filtration
- ❖ Our Predictive & Preventative Maintenance Programme is GUARANTEED to save 15% of your total operating costs

Available in 200L, 20L, 5L, 4 X 5L Containers

Issued January 2026

