

PM313HP

Manual Transmission
High Performance
Fluid GL-4

High Performance Low Viscosity Transmission Fluid

Product Information

PM313HP is a new generation high-performance fluid engineered on group 2 base stocks using the latest in advanced additive technologies and has been designed for the latest high-performance transmissions.

PM313HP is a tough low viscosity fluid that is noted for its ability to reduce stiff or notchy gear change difficulties, (cold shift baulk) associated with the highly variable hot and cold conditions that the Australian climate is noted for.

PM313HP is recommended for manual transmissions, transfer cases in 4x4 applications where called for, transaxle configurations and some automatic transmissions.

PM Lubrication Friction Reduction Technology is Engineered into this Gear Oil.

Typical Properties:

SAE Viscosity	10W30
Kinematic Viscosity	
Visc @ 40°C	85.8 cSt
Visc @ 100°C	11.3 cSt
Pour Point °C	-45
Viscosity Index	120
Density @ 15°C kg/L	0.880
Colour	Red

Exceeds Service Classifications:

- API GL-4
- MIL-L-2105B,C
- Manual Transmission

PM313HP FOR HIGH PERFORMANCE

DO MORE WITH LESS

Benefits:

- Smooth Gear Changes
- Low Viscosity
- Shear Stable
- Reduces Operating Temperature
- Prolonged Service Life
- High Load/High Temperature

Why PM Lubrication?

- ★ Premium Quality
- ★ XPR Protection Reserve
- ★ Cost Effective Lubrication

Available in 205L, 20L, 5L Containers



AUSTRALIAN OWNED

PM Lubrication
4/105 Archibald St, Paget
Queensland 4740 Australia
Tel: 07 4998 5851 Mob: 0419 771 825

www.pmlubrication.com.au hello@pmlubrication.com.au

