

# PM409

**MotorLife Premium**  
**SAE 10W40**  
**API: SN, CF ACEA: A3/B3, A3/B4**  
**ILSAC: GF-5+**

## High Performance – Mixed Fleet

### Product Information

PM409 MotorLife Premium 10W40 provides excellent protection and is formulated using Group 2 Hydrocracked base oil and the latest additive technology. This premium engine oil meets and exceeds the API SN/CF and the latest ILSAC energy-conserving rating, GF-5+. The lubricant will continue to perform under Australia's demanding conditions, including high-temperature highway operation and low-temperature stop-start driving around town. Viscosity shear is minimised, thereby enhancing thermal stability and preventing excessive contamination that can result from regular short runs in a stop-start environment.

PM409 MotorLife Premium 10W40 provides greater protection against oxidation and piston deposits, helping maintain your engine in peak condition for longer. This product will maintain superior lubrication properties under harsh conditions. PM409 MotorLife Premium 10W40 is recommended for four-stroke engines in passenger cars and light commercial vehicles where the manufacturer requires a low-viscosity multi-grade oil or where superior fuel efficiency is needed. PM409 MotorLife Premium 10W40 is suitable for all types of four stroke engine, including diesel, in current and earlier passenger cars, 4WD vehicles, vans and light duty trucks requiring an API: CF or ACEA: B2, B3 specification, operating under vehicle manufacturers' recommended maintenance procedures and exposed to severe and varied conditions, such as high temperature motorway driving or low temperature stop-start driving.

Minimises friction and wear while maintaining power output. Sustains oil pressure.

***Incorporates all of PM Lubrication's Friction Reduction Technology***

### Typical Properties

<b>SAE Viscosity</b>	10W40
<b>Kinematic Viscosity</b>	
Viscosity @ 40 °C	90.6 cSt
Viscosity @ 100 °C	13.5 cSt
TBN	8.31
Pour Point °C	-36
Flash Point °C	TBA
Viscosity Index	143
Ash, Sulphated	0.96%
Density @ 15° C kg/L	0.866

### Meets and or Exceeds Service Classifications

- API: SN, CF
- ACEA: A3/B3, A3/B4
- ILSAC: GF-5+
- Ford Model AU onwards: M2C.153E
- Holden VS & VT Onwards
- Mercedes-Benz 226.0, 229.1
- Nissan
- Rover RES.22.OL. G-4
- VW 500, 501, 505

### PM409 Motor-Life Premium 10W40

### Suitable for Petrol & Diesel Engines in Daily Use

### Benefits

- Reduces Friction and Wear
- Improves Power
- Exceptional Cleanliness
- Lower Wear Rates
- Sustains Oil Pressure
- Minimises Oil Consumption
- Resists Viscosity Thickening

Available in 200L, 20L, 5L, 4 x 5L Containers

### Why PM Lubrication?

- ❖ Premium Quality
- ❖ XPR Protection Reserve
- ❖ Cost Effective Lubrication
- ❖ On-Site Monitoring will maximise equipment life
- ❖ Knife Edge Filtration
- ❖ Our Predictive & Preventative Maintenance Programme is GUARANTEED to save 15% of your Total Operating Costs

Issued January 2026



PM Lubrication  
4/105 Archibald St, Paget  
Queensland 4740 Australia  
Tel: 07 4998 5851 Mob: 0419 771 825  
[www.pmlubrication.com.au](http://www.pmlubrication.com.au) [hello@pmlubrication.com.au](mailto:hello@pmlubrication.com.au)

