

PM414

EnviroTurboLife Extra
SAE 15W/40
API: CI-4, CH-4, SL ACEA: E7, E5

Premium Performance and Protection

Product Information

EnviroTurboLife Extra is an advanced low ash engine oil that meets and exceeds international specifications, with unmatched performance standards including a long service life in high speed 4-stroke naturally aspirated, and turbo-charged diesel and petrol engines in 4,6 & 8 cylinders, multi-cam, multi-valve, common rail and direct injector formats that use a broad range of fuels including gas.

PM414 and its' unique formulation, combined with PM Lubrication's friction reduction technology produces outstanding performance levels in diesel engines fitted with exhaust gas recirculation (EGR) systems and is equipped with the necessary cleaning agents, anti-oxidants and with its higher alkalinity reserve can combat the challenges imposed from the by-products of combustion that can form deposits and incite oil thickening.

The PM XPR, with its heat and shear stable viscosity index improvers, higher load, anti-wear package, and lower coefficient of friction enables the lubricant to counter Australia's harsh conditions. The inbuilt XPR provides greater protection against soot-induced thickening, valve train wear, ring and liner wear, oxidation thickening, and piston deposits. **EnviroTurboLife Extra** is suitable for petrol engines in passenger cars, and light-load diesel, involving such applications as 4WDs and transport, and heavy-duty applications found in buses, agricultural pursuits, mining, and trucking.

PM Lubrication is greatly interested in extending the life of machinery and the return on investment, and so encourages the utilization of micro-depth media filtration. Premium quality lubricants with appropriate filtration will greatly increase the lubricant's life and the serviced componentry.

Typical Properties:

SAE Viscosity	15W40
Kinematic Viscosity	
Viscosity @ 40°C	121.6 cSt
Viscosity @ 100°C	16.4cSt
TBN	10.4
Viscosity Index	145
Ash, Sulphated	1.2%
Density @ 15°C kg/L	0.876
Pour Point °C	-39

Exceeds Service Classifications:

- API CI-4/SL
- ACEA E7, E5, B3, A3
- Cummins CES 20071, 20072, 20076, 20078
- Caterpillar ECF-2
- Detroit Diesel 93K215
- Deutz DQC III-10
- Global DHD-1
- MB 228.3,229.1
- Mack EO-N, EO-M PLUS
- MAN M3275
- MTU Type 2
- Navistar
- Renault Truck RVI, RLD-2
- Volvo VDS3

Benefits:

- Reduces Friction
- Exceptional Cleanliness
- Lower Wear Rates
- Extended Drain Capacity
- Prolonged Service Life
- Resists Viscosity Thickening

Available in 205L, 20L, 5L Containers

PM414 EXTRA
For a long and healthy life

DO MORE WITH LESS

Why PM Lubrication?

- ★ Premium Quality
- ★ Micro-Filtration
- ★ Long Life

Issued on 13/02/2024



PM Lubrication
4/105 Archibald St, Paget
Queensland 4740 Australia
Tel: 07 4998 5851 Mob: 0419 771 825
www.pmlubrication.com.au hello@pmlubrication.com.au

