

PM414

EnviroTurboLife Extra
SAE 15W/40
API CI-4,CH-4,CG-4,CF-4 SL ACEA: E7,E5,E3,B4,B3,A3

Premium Performance and Protection

Product Information

EnviroTurboLife EXTRA is an advanced low ash engine oil developed for petrol, light, and heavy-duty diesel engines with unrivaled performance capabilities in meeting the performance requirements of low emission engines and will achieve improved protection in earlier model engines where emission control measures began taking effect.

EnviroTurboLife EXTRA is recommended for all four-stroke naturally aspirated and turbocharged engines in 4, 6 & 8 cylinder, multi-cam, multi-valve, common rail and direct injection engines..

EnviroTurboLife EXTRA also has an application in petrol engines including LPG fuel.

EnviroTurboLife EXTRA meets every international specification for unsurpassed performance and long service life. This engine oil provides greater wear protection against soot-induced thickening, valve train wear, ring and liner wear, oxidation thickening, and piston deposits.

Vehicle/Fuel Types: EnviroTurboLife Extra is suitable for petrol and light load diesels, including 4WDs and heavier applications found in buses, agricultural applications, and trucking. PM 414, is NOT suitable for emission control systems, including DPF. **Fuel Types:** Diesel, petrol, E10, LPG.

PM Lubrication is greatly interested in extending the life of machinery and the return on investment, and so encourages the utilization of micro depth media filtration. Premium quality lubricants with appropriate filtration will greatly increase the life of the lubricant and the componentry that is serviced.

Typical Properties:

SAE Viscosity	15W40
Kinematic Viscosity	
Viscosity @ 40°C	121.6 cSt
Viscosity @ 100°C	16.4cSt
TBN	10.4
Viscosity Index	145
Ash, Sulphated	1.2%
Density @ 15°C kg/L	0.876
Pour Point °C	-39

Benefits:

- Reduces Friction
- Exceptional Cleanliness
- Lower Wear Rates
- Extended Drain Periods
- Prolonged Service Life
- Resists Viscosity Thickening

Available in 205L, 20L, 5L Containers

Exceeds Service Classifications:

- API CI-4,CH-4, CG-4,CF-4/SL
- ACEA E7,E5,E3,B4.B3,A3
- Allison C4(not 500 series WT transmissions)
- Cummins CES 20071,20072,20076,20078
- Caterpillar ECF-1A,ECF-2
- Deutz DQC 111-10
- Global DHD-1
- MB 228.3,229.1
- Mack EO-N,EO-M,EO-M PLUS
- Navistar
- Renault Truck RLD, RLD-2
- Volvo VDS3

PM414 EXTRA
For performance

DO MORE WITH LESS

Why PM Lubrication?

- ★ Premium Quality
- ★ Micro-Filtration
- ★ Long Life

PM414

EnviroTurboLife Extra

SAE 15W/40

API CI-4,CH-4,CG-4,CF-4 SL ACEA: E7,E5,E3,B4,B3,A3



PM Lubrication
4/105 Archibald St, Paget
Queensland 4740 Australia
Tel: 07 4998 5851 Mob: 0419 771 825
www.pmlubrication.com.au hello@pmlubrication.com.au

