

# PM423

**ENVIRO \*R\* 0/40**  
Full Synthetic Engine Oil  
SAE 0W40 API SN/CF

## Competition - High Performance - Low SAPS Technology

### Product Information

Enviro \*R\* 0/40 is developed for use in competition and high-performance engines including extreme conditions. A full synthetic performance lubricant utilizing a PAO base stock for maximum protection, combining the latest European specification in engine oil formulation and low SAPS additive technology to provide a lubricating oil with the highest level of protection as specified by makers such as BMW, Porsche, and Mercedes and Jeep.

It is specially designed for use in high-performance turbocharged and non-turbo petrol and in diesel engines designed prior to the adoption of particulate filters. PM423 can reduce oil consumption whilst delivering fuel economy benefits through effective friction reduction and load improvement agents.

Enviro \*R\* 0/40 is blended to resist high-temperature deposits and has been developed with an additional anti-wear package to protect in extreme conditions, due to its high molecular weight, the lubricant will continue to hold its character and properties for extended periods of time.

PM423 has the following advantages over conventional mineral and synthetic oil-based products. *\*Superior resistance to oxidation and high-temperature deposits.\* Superior protection under race conditions. \* Improved engine performance.\* Superior film Strength. \* High Viscosity Index - minimal viscosity change at high and low operating temperatures. \*Improved component life. \* Compatibility with seals and coatings.*

Enviro \*R\* is suitable for use in petrol, LPG, and light load diesel engines.

**Developed using PM Lubrication's Friction Reduction Technology.**

**Minimizes friction and wear while maintaining power output. Sustains oil pressure.**

### Typical Properties:

<b>SAE Viscosity</b>	0W40
<b>Kinematic Viscosity</b>	
Viscosity @ 40°C	86 cSt
Viscosity @ 100°C	14.8 cSt
Viscosity Index	180
Sulphated Ash %	0.93
TBN	7.5
Density @ 15° C	0.841
Flash Point °C	228

### Exceeds Service Classifications:

- API SN/CF
- ACEA A3/B3; A3/B4 C3
- BMW LL-01, 04
- FORD WSS-M2C937-A
- ILSAC GF-5
- MB 229.3;229.5
- Porsche A40
- Renault 0700; 0710
- VW 502.00; 505.00

### PM423 ENVIRO \*R\* 0W40

A race-bred lubricant

### Benefits

- Reduces Friction
- Exceptional Cleanliness
- Lower Wear Rates
- Superior Film Strength
- Pleasing Performance

### Why PM Lubrication?

THE Brand with THE Results

- ★ Protects
- ★ Performs
- ★ Peace of Mind
- ★ Produces a Smile.

Available in 5L Container



PM Lubrication  
4/105 Archibald St, Paget  
Queensland 4740 Australia  
Tel: 07 4998 5851 Mob: 0419 771 825  
[www.pmlubrication.com.au](http://www.pmlubrication.com.au) [hello@pmlubrication.com.au](mailto:hello@pmlubrication.com.au)

