

PM425

UniPro Synthetic 5W-30

Full Synthetic Engine Oil

API:SN/CF ACEA: A5/B5 C2 C3 C5 ILSAC GF-5

Full Synthetic for Gasoline, LPG, Light Diesel Mid SAPS Engine Oil

Product Information

Engine technology is experiencing significant advances which are realized in the form of increased power and efficiency, resulting in engines working harder than ever before under demanding conditions. The engine's lubricant is the only thing that allows for the performance we have come to expect from these power sources.

PM425 UniPro Synthetic 5W30 has utilized PM Lubrication's advanced additive technology and high-quality heat stable and shear stable viscosity modifiers to ensure protection against wear, corrosion, oxidation, and piston deposits while maintaining protection in the demanding conditions experienced in Australia.

Application: UniPro Synthetic 5W-30 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an API SN/CF, ACEA A5/B5; C2 C3 C5 ILSAC GF-5+ Mid SAPS lubricant which is found in passenger vehicles fitted with emission control - exhaust treatment systems.

Advantages: PM Lubrication UniPro 5W-30 gives one the confidence in the protection one needs from the highly engineered engines that move us about with efficiency.

** Reduces friction with lower wear rates while maintaining efficiency. **Provides protection in all driving conditions and operating temperatures. **Maintains engine cleanliness. ** Helps provide enhanced fuel efficiency.

Minimizes friction and wear while maintaining power output. Sustains oil pressure.

Typical Properties:

SAE Viscosity	5W30
Kinematic Viscosity	
Viscosity @ 40°C	62.4 cSt
Viscosity @ 100°C	10.7 cSt
Viscosity Index	163
Ash, Sulphated	<0.8
Density @ 15°C kg/l	0.846

Exceeds Service Classifications:

- API SN/CF
- ACEA: A5/B5-12,C2,C3-12,C5-16
- ILSAC GF-5+
- BMW LL04
- Ford WSS-M2C913-D
- GM DEXOS 2
- JAGUAR LAND ROVER STJLR 03.5003
- MB 229.31,229.51,229.52
- PORSCHE A040
- RENAULT RN0700,0710
- VW 502.00; 505.00; 505.01

Benefits:

- Reduces Friction
- Exceptional Cleanliness
- Lower Wear Rates
- Lower Emissions
- Fuel Conservation
- Resists Viscosity Thickening

PM425 UniPro Synthetic 5W-30 for efficiency.

Why PM Lubrication?

- ★ **Guaranteed Cost-Effective**
- ★ **Lubrication, with the adoption of premium quality lubricants and depth media filtration, will extend the life of the lubricant and componentry**

Available in 205L, 20L, 5L Containers



PM Lubrication
4/105 Archibald St, Paget
Queensland 4740 Australia
Tel: 07 4998 5851 Mob: 0419 771 825
www.pmlubrication.com.au hello@pmlubrication.com.au

