

PM425

UniPro Synthetic 5W30
Full Synthetic Engine Oil
API:SN/CF ACEA: A5/B5, C3 ILSAC GF-5

FULL SYNTHETIC FOR GASOLINE, LPG, LIGHT DIESEL MID SAPS ENGINE OIL

Product Information

Engine technology is experiencing significant advances, which are realized in the form of increased power and efficiency, resulting in engines working harder than ever before under demanding conditions. The engine's lubricant is the only thing that allows for the performance we have come to expect from these power sources.

PM425 has been engineered with PM L's XPR Xtra Protection Reserve to meet and exceed the demands of modern engines currently in circulation. Premium quality heat and shear-stable viscosity modifiers are employed to ensure protection against wear, corrosion, oxidation, and piston deposits while maintaining protection in the widely varying and demanding conditions experienced in Australia.

Application: UniPro Synthetic 5W30 is another premium engine oil formulation utilizing PM's advanced lubrication technology that protects modern 4, 6, & 8 cylinder multi-cam, naturally aspirated, supercharged, turbocharged, common rail and direct injection engines found in passenger cars, 4WDs, and light commercials that require this specification. The lubricant provides immediate protection upon startup with a fast flow to critical parts as it transitions to operating temperature. The low tolerances found in modern engines require the use of lower-viscosity engine oils; consequently, the demand on the lubricant increases accordingly, especially concerning the maintenance of viscosity, film thickness, and film strength.

Advantages: PM Lubrication UniPro 5W30 gives one the confidence in the protection one needs from the highly engineered engines that move us about with efficiency.

**** Reduces friction with lower wear rates while maintaining efficiency. **Protects in all driving conditions and operating temperatures. **Maintains engine cleanliness. ** Helps provide enhanced fuel efficiency.**

Minimizes friction and wear while maintaining power output. Sustains oil pressure

Typical Properties:

SAE Viscosity	5W30
Kinematic Viscosity	
Viscosity @ 40°C	62.4 cSt
Viscosity @ 100°C	10.7 cSt
Viscosity Index	163
Ash, Sulphated	<0.8
Density @ 15°C kg/l	0.846

Benefits:

- Reduces Friction
- Exceptional Cleanliness
- Lower Wear Rates
- Lower Emissions
- Fuel Conservation
- Resists Viscosity Thickening

Available in 200L, 20L, 5L, 4 X 5L Containers

Exceeds Service Classifications:

- API SN/CF
- ACEA: A5/B5, C3
- ILSAC GF-5+
- BMW LL04
- Ford WSS-M2C913-D
- GM DEXOS 2
- Jaguar Land Rover STJLR 03.5003
- MB 229.31, 229.51, 229.52
- Porsche A040
- Renault RN0700, 0710
- VW 502.00; 505.00; 505.01

PM425 UNIPRO SYNTHETIC 5W30
Engine Protection & Peace of Mind

Why PM Lubrication?

- ★ Premium Quality
- ★ XPR Protection Reserve
- ★ Cost-Effective Lubrication
- ★ On-Site Monitoring will maximise equipment life
- ★ Knife Edge Filtration

Issued on 3/10/2025



PM Lubrication
4/105 Archibald St, Paget
Queensland 4740 Australia
Tel: 07 4998 5851 Mob: 0419 771 825
www.pmlubrication.com.au hello@pmlubrication.com.au

