PN430 (Formerly R-011)

Product Information

Mono 30 (formerly R-011) is an advanced monograde heavy-duty mineral oil for use in a wide range of petrol and diesel and naturally aspirated engines. The high film strength and load-carrying capacity of this lubricant will see engines experience lower wear rates and improved fuel economy.

Mono 30 combines high-quality paraffinic base oils, anti-wear, foam controlling additives, and high-temperature detergents, oxidation, rust, and corrosion inhibitors to achieve outstanding results in engine cleanliness, and performance. The lubricant also provides outstanding results in carbon deposit control in the upper piston region. The nature and formulation of a monograde produce benefits in the area of oil thinning, oil consumption. Corrosion and rust are also inhibited by this premium lubricant.

Mono 30 through its advanced formulation is a monograde engine oil for use in four-stroke unleaded, and diesel engines, naturally aspirated. Ideally suited to air-cooled stationary motors on pumps, compressors, conveyors, augers, four-stroke lawn mowers where a light viscosity monograde is recommended. This product meets the recommendation for Briggs and Stratton designed and produced engines.

PM Lubrication's Mono 30 minimizes friction and wear while maintaining power output. Sustains oil pressure.

Typical Properties:

SAE Viscosity	30
Kinematic Viscosity Viscosity @ 40°C Viscosity @ 100°C TBN Pour Point °C Flash Point °C Colour Viscosity Index Ash, Sulphated Wt % Density @ 15°C kg/L	107 cSt 11.9 cSt 6.4 -21 228 Natural 101 0.83 0.895

Benefits:

- Reduces Friction
- Exceptional Cleanliness
- Lower Wear Rates
- Lower Emissions
- Fuel Conservation
- Resists Viscosity Thickening

Available in 205L, 20L, 5L Containers

Exceeds Service Classifications:

- API SG, CF-4
- FORD M2C153,M2C101C
- GM 6094M
- JASO MA
- MB 226.1
- MIL-L-46152B, MIL-L-2104E

PM430 MONO 30 - covers a wide range of applications.

Why PM Lubrication?

- ★ Guaranteed Cost-Effective
- ★ Lubrication with the adoption of premium quality lubricants and depth media filtration extends the life of the lubricant and componentry.



PM Lubrication 4/105 Archibald St, Paget Queensland 4740 Australia Tel: 07 4998 5851 Mob: 0419 771 825 www.pmlubrication.com.au hello@pmlubrication.com.au

