

# PM600/50

**Coolcor 50**  
Long Life HDD Coolant PreMix

## Heavy Duty Organic Acid Technology Universal Engine Coolant 1,000,000 kilometres or 12,000 hours

### Product Information

PM600/50 Coolcor Long Life Premix Coolant is a fully formulated heavy duty hybrid technology universal coolant that has been developed to meet engine manufacturers requirements to provide excellent performance in low and high temperature operation and provide the protection required.

Long-life hybrid technology has a decisive advantage in its robustness against conventional and Organic Acid Technology (OAT) engine coolants and is fully compatible with both.

PM600/50 Coolcor Long Life is low in silicates, phosphates and is amine free and is recommended for use in all passenger cars, 4WD's, light and heavy duty diesel applications, including safeguarding aluminium in high temperature zones.

\*\*Coolcor Long Life Premix does not require a charge of supplemental coolant additives,(SCAs), with initial fill, in heavy duty diesel applications as the product has been formulated to protect diesel engine wet sleeve liners.

\*\*Coolcor is compatible with coolant filtration when administered at 50% concentration with deionized water.

### PM600/50 COOLCOR IS A 50/50 COOLANT PREMIX OF LONG LIFE COOLANT AND DEMINERALISED WATER

### Benefits

- |  |  |
|--|--|
| <ul style="list-style-type: none"><li>• Long Life Protection and Performance</li><li>• Low Ambient Temperature Protection</li><li>• Protects Against Corrosion</li><li>• Low in Silicates</li><li>• Phosphate and Amine free</li></ul> | <ul style="list-style-type: none"><li>• Water Pump Lubrication</li><li>• Compatibility With Seals and Hoses</li><li>• Meets or exceeds OEM approvals</li><li>• Universal Use.</li><li>• Glycol Fortified</li></ul> |
|--|--|

### PM600/50 Coolcor Long Life HDD Coolant PreMix meets OEM requirements where called for:

|   |   |   |
|---|---|---|
| ATM D-3306, D-4895, D-6210<br>Caterpillar Sr EC1<br>Cummins 14603<br>Daimler Chrysler MS 7170, MS 9769<br>Detroit Diesel 7SE 298<br>Ford ESE-M97B44A, ESE-M97B18C, WSS<br>M97B51-A1<br>Freightliner 48-2288D<br>GM1825M,1899M, GM Heavy Truck | Hyundai SAE J1034, J1941 JIS<br>K2234,<br>Kenworth RO26-170-97<br>Land Rover<br>Mack Trucks<br>MAN 324<br>Mercedes Benz DBL 325<br>MTU MTL 5048 | New Holland WSN-M97B18-D<br>PACCAR<br>Perkins<br>Peterbilt 8502.002<br>Saab-Scania 6901<br>TMC RP329<br>US Federal A-A-870-A<br>Volvo Heavy Truck<br>White Star |
|---|---|---|

Available in 205L, 20L, 5L Container

### Why PM Lubrication?

Premium Quality  
XPR Protection Reserve  
Cost Effective Lubrication



PM Lubrication  
4/105 Archibald St, Paget  
Queensland 4740 Australia  
Tel: 07 4998 5851 Mob: 0419 771 825  
[www.pmlubrication.com.au](http://www.pmlubrication.com.au) [hello@pmlubrication.com.au](mailto:hello@pmlubrication.com.au)

