# **PM703**

### Multi-purpose Grease with Molybdenum Disulfide

# **Product Information**

PM703 "Molybdenum" grease is a superior multi-purpose Molybdenum Disulphide containing grease having excellent lubrication characteristics for a wide range of plain bearings, kingpins, gears and couplings in automotive, marine, agricultural and industrial and construction equipment applications.

PM703 with extreme pressure and anti-wear properties enable a long service life under high load and shock conditions, in low and high-temperature environments. 703 "Molybdenum" has shear stability and effective anti-rust, anti-corrosion, anti-oxidation inhibitors at work and when combined with tackiness adhesive additives, this product becomes the preferred recommendation for extended life anti-friction bearings. With extended service, it will maintain its original consistency. It will not thin out because of the high resistance to shear. It will not thicken since it resists oxidation.

PM703 has high water resistance and where water washout influences cannot be avoided, even at elevated temperatures, effective lubrication is maintained. In extreme cases where some of the carrier greases have been removed because of severe adverse conditions the "Moly" assists in providing ongoing lubrication. **Recommended applications:** 

For all plain, ball, and roller bearings, particularly those fitted with disc brakes, pins, and bushes, in all automotive, marine, truck, agricultural, and construction equipment. Excellent for ball joints and ensures minimum wear and minimum torque with protection from rust.

NLGI Grade Appearance Texture Viscosity Base Oil 40°C Viscosity Base Oil 100°C Drop Point °C Four-Ball Weld kg/f Four-Ball Scar, mm	2 Dark Grey- Buttery Tacky 210 cSt 18.5 cSt 260+ 315 0.48	Method ASTM 217 ASTM D445 ASTM D445 ASTM D2265 ASTM D2596 ASTM D2266
Rust Prevention Timken OK Load kg	No Rust 23	ASTM D1743 ASTM D2509
Pumpability Oxidation Resist Press Drop	Excellent 15kpa (100 hr)	ASTM D942

#### **Typical Properties:**

## **Benefits:**

- Excellent Stay Put Character
- Reduces Maintenance Costs
- Excellent Lubrication with high water resistance
- DO MORE WITH LESS

Available in 180KG, 20KG, 2.5KG, 450G Containers



PM Lubrication 4/105 Archibald St, Paget Queensland 4740 Australia Tel: 07 4998 5851 Mob: 0419 771 825 www.pmlubrication.com.au hello@pmlubrication.com.au

