

Lithium 12 for Automatic Greasing Systems

Product Information

PM704 EP-0 Grease is an amber Lithium 12 Hydroxy grease that is formulated from the highest quality base oils and fortified with rust and oxidation inhibitors along with extreme pressure additives to ensure high film strength, extreme pressure, and anti-wear properties.

PM 704 EP-0 Grease has an “apple sauce” consistency and is recommended for use with automatic greasing systems that require the correct consistency for trouble-free operation.

Typical Properties

		Method
NLGI Grade	0	ASTM 217
Appearance	Amber	
Texture	Smooth	
Viscosity Base Oil @ 40°C	180-210 cSt	ASTM D445
Viscosity Base Oil @ 100°C	15.5-17.5 cSt	ASTM D445
Drop Point °C	250	ASTM D2265
Four-Ball Weld, kg/f	40	ASTM D2596
Four-Ball Wear Scar, mm	0.45	ASTM D2266
Rust Prevention	Pass	ASTM D1743
Timken OK Load, kg	18.14	ASTM D2509
Viscosity Index	80 min	
Pumpability	Excellent	
Worked Penetration	355-385/60 strokes)	ASTM D1743

PM704 EP-0 Grease

For Automatic Greasing Systems

Why PM Lubrication?

- ❖ Premium Quality
- ❖ XPR Protection Reserve
- ❖ Cost Effective Lubrication
- ❖ On-Site Monitoring will maximise equipment life
- ❖ Knife Edge Filtration
- ❖ Our Predictive & Preventative Maintenance Programme is **GUARANTEED** to save 15% of your total operating costs

Benefits

- Automatic Greasing
- Increase Bearing Life with Optimum Delivery via Precise Metering
- Reduces Maintenance Costs
- DO MORE WITH LESS

Available in 20KG, 450G, 500G Containers

Issued 7/02/2026



PM Lubrication
4/105 Archibald St, Paget
Queensland 4740 Australia
Tel: 07 4998 5851 Mob: 0419 771 825
www.pmlubrication.com.au hello@pmlubrication.com.au

