

Lithium 12 for Automatic Greasing Systems

Product Information

PM704 EP-0 is an amber Lithium 12 Hydroxy grease that is formulated from the highest quality base oils and fortified with rust and oxidation inhibitors along with extreme pressure additives to ensure high film strength, extreme pressure, and anti-wear properties.

PM EP-0 is an "apple sauce" consistency and its formulation is recommended for use with automatic greasing systems that require the correct consistency formulation for trouble-free operation.

Typical Properties:

		Method
NLGI Grade Appearance Texture Viscosity Base Oil 40°C Viscosity Base Oil 100°C Drop Point °C Four-Ball Weld, kg/f Four-Ball Scar, mm Rust Prevention Timken OK Load, kg Viscosity Index Pumpability Worked Penetration	0 Amber Smooth 180-210 cSt 15.5-17.5 cSt 250 40 0.45 Pass 18.14 80 min Excellent 355-385/60 strokes	ASTM 217 ASTM D445 ASTM D445 ASTM D2265 ASTM D2596 ASTM D2266 ASTM D1743 ASTM D2509 ASTM D1743

Benefits:

- Automatic Greasing
- Increase bearing life with
- Optimum delivery via precise metering
- Reduces Maintenance Costs
- DO MORE WITH LESS

Available in 20KG, 2.5KG, Containers



