

Lithium 12 for Automatic Greasing Systems

Product Information

PM706 EP-00 Grease is an amber Lithium 12 Hydroxy grease that is formulated from the highest quality base oils and fortified with rust and oxidation inhibitors along with extreme pressure additives to ensure high film strength, extreme pressure, and anti-wear properties.

706 EP-00 Grease has an “apple sauce” consistency and is recommended for use with automatic greasing systems that require the correct consistency for trouble-free operation.

Typical Properties

| | | Method |
|--------------------------|--------------------|------------|
| NLGI Grade | 00 | ASTM 217 |
| Appearance | Amber | |
| Texture | Smooth | |
| Viscosity Base Oil 40°C | 180-210 cSt | ASTM D445 |
| Viscosity Base Oil 100°C | 15.5-17.5 cSt | ASTM D445 |
| Drop Point °C | 250 | ASTM D2265 |
| Four-Ball Weld, kg/f | 40 | ASTM D2596 |
| Four-Ball Scar, mm | 0.45 | ASTM D2266 |
| Rust Prevention | Pass | ASTM D1743 |
| Timken OK Load, kg | 18.14 | ASTM D2509 |
| Viscosity Index | 80 min | |
| Pumpability | Excellent | |
| Worked Penetration 25°C | 400-430/60 strokes | ASTM D1743 |

PM706 EP-00 Grease

For Automatic Greasing Systems

Why PM Lubrication?

- ❖ Premium Quality
- ❖ XPR Protection Reserve
- ❖ Cost Effective Lubrication
- ❖ On-Site Monitoring will maximise equipment life
- ❖ Knife Edge Filtration
- ❖ Our Predictive & Preventative Maintenance Programme is GUARANTEED to save 15% of your total operating costs

Benefits

- Automatic Greasing
- Increase Bearing Life with Optimum Delivery via Precise Metering
- Reduces Maintenance Costs
- DO MORE WITH LESS

Available in 20KG, 2.5KG, 450G, 20 x 450G Containers

Issued 7/02/2026



PM Lubrication
4/105 Archibald St, Paget
Queensland 4740 Australia
Tel: 07 4998 5851 Mob: 0419 771 825
www.pmlubrication.com.au hello@pmlubrication.com.au

